![Vivitek logo] Vivid Color, Vivid Life

Portable Projector

Vivitek DX273

XGA projector with a brilliant image, multiple I/O ports and long-life lamp

Features

- High 4,000 lumens of brightness for projection even in bright meeting rooms
- Great 20,000:1 contrast ratio ensuring clear presentations and sharp text
- Native XGA (1024 x 768) resolution up to maximum WUXGA (1,920 x1,200)
- DLP® and BrilliantColor™ technologies for distinct and vibrant images
- Low cost of ownership and maintenance with an energy efficient lamp for up to 10,000 hours (Dynamic Eco. Mode) of usage
- 6 segment (RGBYCW) color wheel for improved and vivid color reproduction
- 3D Ready via DLP® Link™ and HDMI v.1.4
- Audio ready with 2 watt audio speaker and audio-in/out ports
- Quiet operation with low 29dB (Eco mode) acoustic noise
- Top sided lamp cover for simple lamp removal and insertion
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington® security slot, security bar, and power button lock

Specifications

Display Type	Single Chip 0.55" DLP Technology by TI
Brightness	4,000 Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	WUXGA (1,920 x 1,200)
Contrast Ratio	20,000:1
Lamp Life/Type	5,500/7,000/10,000 Hours (Normal/Eco./Dynamic Eco. Mode), 210W
Throw Ratio	1.94 - 2.33
Image Size (Diagonal)	40" - 300"
Projection Distance	1.6m -12.2m (5.2ft - 40ft)
Projection Lens	F=2.42 – 2.62, f=22.5 – 25.79mm
Zoom Ratio	1.2x
Aspect Ratio	4:3
Offset	106%±5%
Keystone Correction	Vertical:±40°
Horizontal Frequency	15 -102kHz
Vertical Frequency	23 - 120Hz
3D Compatibility	Yes
Speaker	2W (Mono)
Computer Compatibility	VGA (640 x 480) to WUXGA_RB(1920 x 1200)
Video Compatibility	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
I/O Connection Ports	HDMI v1.4b (x2) (HDCP v1.4 Compliant), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (WxDxH)	331 x 244 x 105mm (13" x 9.6" x 4.1")
Weight	2.6kg (5.7lbs)
Available Colors	White
Noise Level	32dB/29dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Lamp

©2020 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.

![DLP Texas Instruments logo] ![BrilliantColor logo] ![DLP 3D Ready logo] ![HDMI logo]

Photos