

Versatile Business Presentation Tool **Visual Presenter MO-1**

can be used in various business situations.

Show documents, small items and operation of the small equipment clearly on the monitor or screen. Provide persuasive power and increase the depth of understanding of your presentation. Light weight with compact design, you can carry the MO-1 wherever you need to go. Take it with you for important meetings with your clients or even on business trips.


Use the MO-1 during meetings for unlimited purposes, such as to review written contracts, to magnify small product parts, to demonstrate smart phones or tablets, or even as a web cam for online meetings. Furthermore, you can use the MO-1 as a scanner to transform documents, architectural models and product parts into digital data instantly.

What is a Visual Presenter?

A visual presenter is an image capture device used to project the images of documents and three monitor. The equipped zoom lens allows you to adjust the size of the image as you wish. A visual presenter can also be called a document camera or visualizer.



•Wireless model: MO-1w / Receiver: VPR-1



MO-1/MO-1w Specifications

Model	MO-1	MO-1w
Power source	DC5V(AC adapter) / Power supply from USB (USB operation only)	
Power consumption	4.2W(Standby 0.25W)/ USB 3.3W	7.4W(Standby 0.15W)/ USB 3.5W
lmage pick-up element	1/3.2" 5M pixel CMOS Sensor	
Effective pixels	Horizontal 2048, Vertical 1536	
Lens	F2.9	
Shooting area	Max.257mmx342mm (10 7/64" x 13 15/32")(WXGA/ XGA/ VGA	
Focus	AF(One-push)/ MANUAL	
White balance	AUTO/ MANUAL	
Digital zoom	8 x	
Flicker correction	Provided	
HDMI output	1080i (30fps), 720p (30fps)	N/A
	720p (60fps)*	
Analog RGB output	WXGA/ XGA (20fps)	N/A
	When power is OFF: External RGB input	
	(Only when AC adapter is used)	
USB output	Type B(Mini), WXGA/ XGA (20fps), VGA (20fps),	
	1080p (15fps), 720p (30fps)	
WHDI output (Uncompressed wireless image transmission)	N/A	WXGA/ XGA, 1080i(30fps)
wireless image transmission)		720p(30fps)/ 720p(60fps)*
Input selection	HDMI/ RGB/ USB/ External	WDHI/ USB/ External
Input terminal	Analog RGB(D-Sub), HDMI(Type A(standard)HDMI compliant)	
Image rotation	Provided Camera Still image : 0'/90'/180'/270°	
	Camera live image : 0°/180°	
Microphone	Built-in (USB/ HDMI)	Built-in (USB/ WHDI)
Still image capture	Provided	
SD card slot	Provided	
Illumination	White LED	
Weight	550g (1.2lbs)	590g (1.3lbs)
Accessories	AC adapter/ Power cord/ CD-ROM (Application software	
	"Image Mate"/ Instruction manual/ Quick start guide)/	
	USB cable/ Safety instructions	

ELMO's Helping to Provide a Greener Future for Our Children

ertain Hazardous Substances in electronic equipment). This compliance helps to ensure a ealthier and greener environment for all our children

VPR-1 Specifications

Operating temperature	0°C~40°C	
Operating frequency	5190MHz ~ 5670MHz	
Communication distance	Approx. 10m (32.8feet) (Varies depending on the operating environment.)	
Power source	AC adapter	
	Input : 100V-240V, 0.5A, 50/60Hz	
	Output:5V,2A	
Standards	Compliant with HDMI / WHDI standards, Supports HDCP	
Transmitter registration	Max. 8 units	
HDMI OUT (Type A)	VGA (640x480)60Hz/75Hz, SVGA (800x600)60Hz/75Hz,	
	XGA (1024x768) 60Hz/75Hz, WXGA (1280x768) 60Hz,	
	WXGA (1280x800) 60Hz, SXGA (1280x1024) 60Hz/75Hz	
	1152x864 (60Hz), 1280x960(60Hz)	
	480p, 576p, 720p, 1080i, 1080p	
	192 kHz x 24 bit	
Power consumption	5.5W (5V / 1.1A) (Excluding the AC adapter)	
Dimensions	L83 x W80 x H31 (mm) L 3 1/4" x W 3 1/8" x H 1 1/4"	
Weight	110g (0.24lbs)	



introduces you to the useful and effective ways of using the document camera and how the ELMO document camera is used and supported by teachers worldwide. http://www.elmoglobal.com



ISO 9001


ELMO CO., LTD. 6-14, Meizen-cho, Mizuho-ku Nagoya, 467-8567, Japan E-mail: overseassales@elmo.co.jp





Printed in Japan (KW) 03/2012

ELMO






Visual Presenter MO-1



©High-precision visual presentation tool




Full-HD megapixel CMOS sensor

Full motion video

Digital zoom

Reproduce objects in true color while showing details clearly. High definition and smooth video image can be fully displayed on an HD TV screen.

○Simple data import to a computer



MO-1 can be used as a three dimensional

scanner. (Close-up to 7cm (2 3/4")

distance from the objects.)

Camera head



SD card slot

Still images can be stored on the SD card.



HDMI input/output

is possible.




Add more impact to your presentation with the CRA-1 wireless tablet!

CRA-1 allows you to easily make annotations on live images. Make your presentation more engaging and effective.

Network communication tool



Built-in Microphone allows you to use the MO-1 as a web cam for important online meetings.



OMO-1's other useful features

Interface



Powered via USB*

High definition image presentation No AC adapter is required when the MO-1 is connected to a computer by the USB cable.

*when in USB mode

