



Chromebox Mini

An Enterprise Ready Solution Running on Chrome.

Small, but powerful: the smallest enterprise-ready Chromebox today, designed for the signage, POS, corporate and kiosk markets. Empower customers with ease of experience and greater control of in-store engagement.

The AOPEN Chromebox Mini is a highly reliable and powerful enterprise grade solution that operates 24/7 under tough conditions (up to 40°C). It sets itself apart from any Chromebox, being the most flexible of its kind. The small size combined with strong computing power creates the perfect solution for any commercial or corporate environment. The Chromebox Mini ensures a speedy, simple, secure and scalable solution.


Deployment and management of the devices has never been easier using Chrome Device Management. This easy and powerful tool allows users to remotely manage entire fleets of AOPEN Commercial Chrome devices. The advantages of the Chromebox Mini:

- Tough and tamperproof design for 24/7 operability in commercial and public environments (<40°C/104°F)
- Smallest chrome form factor available in the market today, for easy integrations
- A cost-effective solution for lower TCO
- The solid-state and fanless design ensure a first-rate performance in ruggedized environment
- AC Power Auto Recovery (APAR)
- Included dual band antenna offers a wide reach
- Kiosk and POS device extensions via commercial converts
- Optional Chrome Device Management on request to save valuable time, costs on installation, programming and maintenance









Chromebox Mini

| Specifications | | | Front Panel I/O | USB 2.0 port | support BC1.2 x 3 | |
|----------------------|-----------------------|--|----------------------|--|--|--|
| | | The most flexible Enterprise Ready Grade Solution in | Front Panel I/O | Power Button with LED | x 1 | |
| Features | | the market today. Running on the Chrome OS. APAR (AC Power Auto Recovery) | | Power switch | x 1 | |
| Commencial Foothware | | Operating Shock 8G, Operating Temperature up to | | HDMI | x 1 | |
| Commercial Features | | 40°C/104°F | Real Panel I/O | Ethernet RJ45 | x 1 | |
| Operating System | | Chrome OS | | Audio Combo Jack | x 1 (Line out/Line in) | |
| CPU | | Rockchip RK3288C Quad-Core Cortex-A17 turbo up to 1.8GHz | | WiFi | BT4.0 : 802.11 b/g/n | |
| | | | | Antenna hole | x 2 | |
| Graphics | | ARM Mali-T764 MP4 GPU clocked at 600 MHz | | Wide Votage Range DC input | DC 12~60V power inlet Jack x 1 | |
| Memory | | Dual Channel 4GB LPDDR3 Memory down design | Environment | Operating Temperature | 0°C ~ 40°C 32°F ~ 104°F | |
| Storage | | EMMC 5.0 16 GB | | Storage Temperature | -20°C ~ 60°C -7°F ~ 140°F | |
| LAN | | Gigabit | | | | |
| | | 10/100/1000 Mbps | | Relative Humidity | 90%@50°C | |
| Form Factor | Dimensions (WxDxH) | 146 x 93 x 24 mm 5.75 x 3.8 x 0.94 inch | | Vibration | Random 2Grms | |
| | Net Weight | 403g | | | User Manual Power Cord/ Power Cord Clip 40W AC to DC 19V Adapter | |
| | Color | Black | Accessories | | | |
| Display | | GPU with ARM Mali-T764 GPU, with TE, ASTC, AFBC technology (Images & Basic HTML only). Limited Video Playback Up to 1080p display resolution Image enhancement processor | | | 2.4/5G dual band Antenna (x 2) | |
| | | | Optional Accessories | | POS peripheral connectors: Mounting Rails | |
| Audio | | Maxim MX98090 | Warranty | | The Chromebox Mini comes with a 1 year warranty. Extended warranty optional for 3 years. | |
| Networking | | Giga LAN Realtek RTL8211E-VB with LED indicate Wi-Fi+ Bluetooth; Wireless 802.11 b/g/n/ac + BT4.0 | For more inform | For more information on Chrome Mini products, visit us at www.aopen.com/chrome | | |